

Shutters FR



From traditional to contemporary, casual to formal, you can add dramatic light control with our energy efficient Shutters. Our shutters combine the traditional warmth and beauty of natural wood with the practical advantage of high-tech materials and design. Ruggedized cap stock enhances surface integrity to resist moisture, heat, UV rays and always stays dry making it the perfect solution for high humidity areas. No fading, chipping, warping or denting. Shutters....timeless beauty then and now.

Features

- 2 1/2, 3 1/2 and 4 1/2 inch louvers
- Resists moisture, heat and UV rays
- Light weight, will not chip, warp, fade or dent
- High thermal insulation value for energy efficiency
- Fire-retardant passes NFPA 701



Color Selection




Antique
042



Arctic
275



Caramel
6119



Cherry
536



Coffee
578



Ebony
215



Espresso
293



Golden
180



Merlot
6304



Walnut
247

Product Specifications

PANEL CONFIGURATIONS

APPLICATIONS:

Inside Mount Windows
Outside Mount Windows
Patio Doors

FRAME STYLES

- L Frame (outside mounts)
- Curved L frame (outside mount)
- Small & Large Z frame (inside mount)
- Designer frame (inside mount)
- Sill frame (for window sills)
- Hang strip only (inside mount, no frame)

AVAILABLE CONFIGURATIONS

- Standard Hinge Systems
- By fold Systems
- By Pass System

Standard Panels:

Louver Size: 2 ½" 3 ½" 4 ½"

WIDTH

Min Panel Size (single panel) 12" 12" 12"
Max Panel Size (single panel) 28" 30" 32"

Max Panel Size (Bifold) 20" 20" 20"

HEIGHT

Min. Panel Height: 20" 20" 20"
Max Panel Height: 120" 120" 120"
Panels over 60" require divider rail

Non-Mortise Hinge Colors:

- Color Coordinated to louver color
- Brass Plated

